



15-SERIES

Rugged, Reliable, Resilient & Robust

The 15-Series Chassis is a commercial base, 4x4 platform truck chassis engineered to the needs of energy, mining, industrial and government customers around the world.

PERFORMANCE IN EXTREME ENVIRONMENTS


Enhanced powertrain, cooling & engine performance

Fully-assembled unit or knockdown kit



15-SERIES

Rugged, Reliable, Resilient & Robust



SPECIFICATIONS

Up to 22,500 lb (10,206 kg) GVW 7,765 lb. (3,522 kg) Chassis Weight 4,200 lb. (1,905 kg) Towed Load Allowance 40 in. (102 cm) cargo bed height at GCW

POWERTRAIN

Electronic-controlled 6-speed automatic transmission 2-speed transfer case, ratios: high - 1:1, low -2.72:1 Hypoid front & rear differentials; 3.08:1 ratio V8, 6.5L turbocharged diesel engine 250 hp (186 KW) @ 3,200 rpm 550 lb-ft (746 N•m) @ 1,800 rpm torque 30 gal. (114 L) fuel capacity **ELECTRICAL** Dual Voltage 14V/28V 400-amp alternator **MOBILITY** 73.6 in. (187 cm) track width 136.3 in (346 cm) wheelbase 26.5 ft. (8.08 m) turning radius 16 in (41 cm) ground clearance 60° angle of approach 45° angle of departure 19° ramp breakover angle 60% grade capability 40% side slope capability (at GCW) 70 mph (113 kph) maximum speed 18 in. (46 cm) vertical step Non-Directional Cross-Country Tread 365/80 R20 tires Front & rear disc service brakes; dual master cylinder with ABS 30 in. (76 cm) deep water fording





AM General Headquarters 105 N. Niles Ave South Bend, IN 46617 (574) 237-6222

www.amgeneral.com