

# HUMVEE®



## 2-CT™ AMBULANCE-i

Built to operate at isolated locations all over the world, the 2-CT™ Ambulance-i is ready to respond to medical emergencies in extreme environmental conditions.

The ambulance features aluminum panels riveted and bonded to a high-strength aluminum alloy frame, and is capable of transporting up

to four litter patients, six ambulatory patients—or a combination of both—as well as medical personnel, equipment and a driver.

Fitted with heating and air conditioning systems, as well as medical oxygen equipment, this ambulance reliably transports casualties from the battlefield to medical aid stations.

---

**RUGGED**  
MEDICAL TRANSPORTATION

*Crew Comfort*  
*Off-Road Mobility*  
*Transportability*

---

**AM General®**



# 2-CT™ AMBULANCE-i



## Vehicle Specifications

### GVW

6,101 kg (13,450 lb.)

### PAYLOAD

2,101 kg (4,633 lb)

### POWERTRAIN

4-speed automatic transmission

2-speed transfer case, ratios:  
high - 1:1, low - 2.72:1

Hypoid front & rear differentials; 3.08:1 ratio

V8, 6.5L turbocharged diesel engine

190 hp (142 KW) @ 3,400 rpm

380 lb-ft (515 N•m) @ 1,700 rpm torque

25 gal. (95 L) fuel capacity

### ELECTRICAL

Dual Voltage 14V/28V

### MOBILITY

48° angle of approach

38.2° angle of departure

25° ramp breakover angle

45.72 cm (18 in.) vertical step

16.5 x 8.25 x 6.5 BC tires

0.76 m (30 in.) deep water fording (1.52 m (60 in.)  
w/ Kit)

## Shelter Specifications

### WEIGHT

1,037.3 kg (2,286.9 lb.)

### DIMENSIONS

Height: 171 cm (67.5 in.)

Width: 213 cm (84.0 in.)

Length: 351 cm (138.0 in.)

Rear Door Opening: 203 cm (80.0 in.)

### OUTER SKIN & FRAME

Aluminum panels are riveted and bonded to high-strength aluminum alloy extrusions

Optional corrosion protection

### ELECTRICAL

12-Volt DC, 115-Volt / 60-Hz AC, and 230-Volt / 50-Hz AC outlet receptacles

### TRANSPORTABILITY

MIL STD 1366 compliant for transportability  
When mounted to a 2-CT (M1152 HMMWV), the entire vehicle is C-130 RORO capable

### FEATURES

Ceiling hooks for intravenous bottles and bags

LED overhead and rear loading lights

One oxygen container; space for up to three

Bulkhead-mounted swivel-style oxygen flow meters with integral adapters

Bubbled aluminum foil insulation

Heavy-duty air conditioning and heating system

Storage for ground ambulance kit

The 2-CT™ Ambulance is manufactured by AM General under a contract with the United States Army and built specifically in accordance with specifications provided to AM General by the U.S. Army. The red cross depicted in these materials is an independent licensed trademark of the International Red Cross and is applied to the vehicles manufactured by AM General in accordance with contract specifications.



AM General Headquarters

105 N. Niles Ave  
South Bend, IN 46617  
(574) 237-6222

[www.amgeneral.com](http://www.amgeneral.com)