

HUMVEE 2-CT[™]

U.S. MILITARY DESIGNATION: HMMWV M1152

Designed to carry nearly the weight of another vehicle, the flexible 2-CT can be equipped with a 9-soldier safety-enhanced troop kit and a variety of command, control, and electronic equipment shelters.



With more than 300,000 vehicles worldwide, **parts commonality** and platform familiarity allows for easy maintenance anywhere in the globe



Features a rugged chassis and powerful engine designed for **scalable protection**, ensuring a dependable truck in the harshest, most demanding environments



Ready to meet multiple mission sets, this vehicle is **transportable** by land, sea, and air





GVW

USA, all configurations: 12,100 lb. (5,488 kg) International, all configurations: 13,500 lb. (6,124 kg)

PAYLOAD

USA

Base vehicle: 5,100 lb. (2,313 kg) w/A-Kit: 5,000 lb. (2,268 kg) w/A- and B-Kits: 3,340 lb. (1,515 kg)

International

Base vehicle: 6,920 lb. (3,139 kg) w/A-Kit: 6,220 lb. (2,821 kg) w/A- and B-Kits: 4,560 lb. (2,068 kg)

POWERTRAIN

4-speed automatic transmission

2-speed transfer case, ratios: high - 1:1, low - 2.72:1

Hypoid front & rear differentials; 3.08:1

V8, 6.5L turbocharged diesel engine 190 hp (142 KW) @ 3,400 rpm 380 lb-ft (515 N•m) @ 1,700 rpm torque 25 gal. (95 L) fuel capacity

ELECTRICAL

Dual Voltage 14V/28V

MOBILITY

Seating for two soldiers

Aggressive angles of approach, departure, and ramp breakover


High climb capacity

37 x 12.5R-16.5 tires

Integrated deep water fording; increased capability with kit



SCALABLE PROTECTION









W/ A-KIT

Enhanced armor in specific vehicle areas



W/ B-KIT

Adds plant- or field-installable perimeter protection (requires A-Kit)



W/FRAG 5

Enhanced perimeter protection and additional armoring points (requires A- and B-Kits)